

Silver Creek Marine Flat bottom pontoons

(All pricing subject to change, confirmed at time of order)

Please note: Our pontoon frames are supplied as a “kit” for the customer to finish however they choose. The total buoyancy is the approximate amount of weight required to fully submerge both pontoons, as supplied with the bare frame. Extra weight from the deck, console, furniture, railings, additional structures, motor, etc will lower this amount. For an **approximate safe load limit** you will need to deduct the weight of any additional items and then divide this number that you get by 2. Silver Creek Marine Ltd. takes no legal responsibility for the use of these kits, which may result in injury or death. For additional information on the proper loading of a pontoon boat you can consult the [Canadian Construction Standards for Small Vessels \(2010\)](#) or hire a naval architect.

Specifications:

- Pontoon material: 1/8" 5052 H32
- Cross members: 2" x 2" x 1/8" - 6061 rectangular tube. 16" apart on center
- Pontoon Height: 18.5"
- Pontoon Width 20"
- Includes a small motor bracket suitable for 10hp or less outboard motor
- Total Height (pontoon height + frame height): 19.5"

For pontoons without a curved bow section (for use as a dock) remove \$500

10' Long x 8'4": \$3, 700 + tax

- Approx weight 375 lbs
- * Total Buoyancy: 2600 lbs *
- 10'4" wide add \$250

15' Long x 8'4": \$5, 150 + tax

- Approx weight 550 lbs
- * Total Buoyancy: 4080 lbs *
- 10'4" wide add \$350

20' Long x 8'4": \$6, 700 + tax

- Approx weight 700 lbs
- * Total Buoyancy: 5500 lbs *

- 10'4" wide add \$400

25' Long x 8'4": \$8, 250 + tax

- Approx weight 875 lbs
- * Total Buoyancy: 6900 lbs *
- 10'4" wide add \$500

30' Long x 8'4": \$10, 550 + tax

- Approx weight 1050 lbs
- * Total Buoyancy: 8400 lbs *
- 10'4" wide add \$600